




MALZEME	Bakır (E-Cu), Kalay Kaplı
İZOLASYON	PVC
ÇALIŞMA SICAKLIĞI	Maksimum 75 °C 600 Volt



ÇATAL TİP İZOLELİ KABLO UÇLARI

DIN 46228

KABLO KESİTİ (mm ²)	ÜRÜN KODU	RENK	CİVATA M	BOYUTLAR							KUTU İÇERİĞİ	KOLİ İÇERİĞİ	KUTU AĞIRLIĞI (gr)
				l	d2	d3	d1	d4	a	s			
0,50-1,50	CK-301KPVC		M3	16,0	3,2	6,0							200
	CK-401KPVC		M4	17,0	4,3	6,8	1,6	4,0	10,5	0,8	200	12000	200
	CK-501KPVC		M5	18,0	5,3	10,0							229
	CK-601KPVC		M6	20,0	6,5	11,0							242
1,50-2,50	CK-302MPVC		M3	18,0	3,2	5,5						12000	197
	CK-402MPVC		M4	17,0	4,3	6,8	2,3	4,5	11,0	0,8	200		202
	CK-502MPVC		M5	19,0	5,3	10,0						10000	265
	CK-602MPVC		M6	21,0	6,5	11,0							297
4,00-6,00	CK-406SPVC		M4	21,0	4,3	8,0							200
	CK-506SPVC		M5	22,0	5,3	10,0						6000	226
	CK-606SPVC		M6	23,0	6,5	11,0	3,6	6,3	13,5	1,0	100		235
	CK-806SPVC		M8	26,0	8,4	14,0						5000	284
	CK-1006SPVC		M10	28,0	10,5	18,0						2500	197