




MALZEME	Bakır (E-Cu), Kalay Kaplı
İZOLASYON	PVC
ÇALIŞMA SICAKLIĞI	Maksimum 75 °C 600 Volt



YUVARLAK TİP İZOLELİ KABLO UÇLARI

DIN 46237

KABLO KESİTİ (mm ²)	ÜRÜN KODU	RENK	CİVATA M	BOYUTLAR							KUTU İÇERİĞİ	KOLİ İÇERİĞİ	KUTU AĞIRLIĞI (gr)
				l	d2	d3	d1	d4	a	s			
0,50-1,50	YK-301KPVC		M3	16,5	3,2	6,0							182
	YK-401KPVC		M4	17,5	4,3	8,0							206
	YK-501KPVC		M5	18,5	5,3	10,0	1,6	4,0	10,5	0,8	200	12.000	238
	YK-601KPVC		M6	22,5	6,5	10,0							255
	YK-801KPVC		M8	22,5	8,4	14,0							324
1,50-2,50	YK-302MPVC		M3	17,0	3,2	6,0						12.000	202
	YK-402MPVC		M4	18,0	4,3	8,0							224
	YK-502MPVC		M5	20,0	5,3	10,0					200		269
	YK-602MPVC		M6	21,0	6,5	11,0	2,3	4,5	11,0	0,8		10.000	297
	YK-802MPVC		M8	22,5	8,4	14,0							346
	YK-1002MPVC		M10	25,5	10,5	18,0					100	5.000	253
	YK-1202MPVC		M12	25,5	13,0	18,0						6.000	200
4,00-6,00	YK-406SPVC		M4	21,0	4,3	8,0							205
	YK-506SPVC		M5	22,5	5,3	10,0						6.000	223
	YK-606SPVC		M6	23,5	6,5	11,0	3,6	6,3	13,5	1,0	100		249
	YK-806SPVC		M8	26,5	8,4	14,0						5.000	290
	YK-1006SPVC		M10	28,5	10,5	18,0							351
	YK-1206SPVC		M12	28,5	13,0	18,0					50	3.000	172