




MALZEME	Bakır (E-Cu), Kalay Kaplı
İZOLASYON	Naylon
ÇALIŞMA SICAKLIĞI	Maksimum 105 °C 600 Volt



İZOLELİ ÇİFT GİRİŞLİ KABLO YÜKSÜKLERİ

DIN 46228

KABLO KESİTİ (mm ²)	ÜRÜN KODU	RENK	BOYUTLAR							KUTU İÇERİĞİ	KOLİ İÇERİĞİ	KUTU AĞIRLIĞI (gr)
			F	L	B	W	D	C				
2 x 0,50	UY-23005	 Beyaz	8,0	14,5	6,5	5,0	1,8	1,5	500	30.000	107	
2 x 0,75	UY-23007	 Mavi	8,0	14,7	6,7	5,5	2,1	1,8	500	30.000	121	
2 x 1,00	UY-23010	 Kırmızı	8,0	15,1	7,1	5,5	2,4	2,1	500	30.000	137	
2 x 1,50	UY-23015	 Siyah	8,0	15,5	7,5	6,4	2,6	2,3	500	25.000	164	
2 x 2,50	UY-23025	 Gri	10,0	18,5	8,5	8,0	3,3	2,9	250	12.500	137	
2 x 4,00	UY-23040	 Turuncu	12,0	23,1	11,1	8,8	4,2	3,8	100	6.000	98	
2 x 6,00	UY-23060	 Yeşil	14,0	26,1	12,1	9,5	5,3	4,9	100	5.000	149	
2 x 10,00	UY-23100	 Kahve	14,0	26,6	12,6	12,6	6,9	6,5	50	2.500	108	
2 x 16,00	UY-23160	 Bej	14,0	31,3	17,3	19,0	8,7	8,3	50	2.500	56	